

PDU20BHVIEC12R/PDU20BHVIEC12Ra  
PDU10BVHVIEC20F/PDU20BVHVIEC24F

### ENTRY-LEVEL POWER DISTRIBUTION

#### Provides reliable power distribution for connected equipment

Ideal for server room and IT applications, the Basic PDU Series is a power distribution device that delivers electricity from a single source to multiple devices. The products feature overload protection, external site ground pin, industrial-grade metal housing, adjustable mounting brackets, long input power cord, and cord retention tray.

#### APPLICATION





- Office
- Back Office
- Server Room
- Data Center
- Factory
- Workstations

#### SERIES FEATURES

- Overload Protection
- Enclosure Construction
- Industrial-grade Metal Housing
- Cord Retention Tray

#### PRODUCT CALLOUTS

1. AC Inlet
2. Output Circuit Breaker
3. Ground Stud
4. AC Outlets
5. Cord Retention Tray Screw Holes





## TECHNICAL SPECIFICATIONS

| Model Name                                       | PDU20BHVIEC12R    | PDU20BHVIEC12Ra           | PDU10BVHVIEC20F           | PDU20BVHVIEC24F           |
|--------------------------------------------------|-------------------|---------------------------|---------------------------|---------------------------|
| <b>Input</b>                                     |                   |                           |                           |                           |
| Nominal Input Voltage (Vac)                      | 200 - 240         | 200 - 240                 | 200 - 240                 | 200 - 240                 |
| Input Frequency (Hz)                             | 50 / 60           | 50 / 60                   | 50 / 60                   | 50 / 60                   |
| Maximum Input Current (A)                        | 16                | 16                        | 10                        | 16                        |
| Input Connector Type                             | IEC C20 x 1       | IEC C20 x 1               | IEC C14 x 1               | IEC C20 x 1               |
| Power Cord Length (m.)                           | 3.05              | 3.05                      | 3.05                      | 3.05                      |
| <b>Output</b>                                    |                   |                           |                           |                           |
| Over Current Protection (Each Bank) (A)          | 16                | 16                        | 10                        | 16                        |
| Outlets - # of Bank(s) (Bank)                    | -                 | 1                         | 1                         | 1                         |
| Outlet(s) - Total                                | 12                | 12                        | 20                        | 24                        |
| Outlet(s) - Front                                | -                 | -                         | 20                        | 24                        |
| Outlet(s) - Rear                                 | 12                | 12                        | -                         | -                         |
| Outlet Type                                      | IEC C13 x 12      | IEC C19 x 2, IEC C13 x 10 | IEC C19 x 4, IEC C13 x 16 | IEC C19 x 4, IEC C13 x 20 |
| <b>Physical</b>                                  |                   |                           |                           |                           |
| Installed Rack Height (U)                        | 1                 | 1                         | 0                         | 0                         |
| Cord Retention Tray                              | Yes               | Yes                       | Yes                       | Yes                       |
| <b>Physical Size</b>                             |                   |                           |                           |                           |
| Dimensions (WxHxD) (mm.)                         | 445 x 44.5 x 38.1 | 445 x 44.5 x 38.1         | 44.5 x 914.4 x 38.1       | 44.5 x 1219.2 x 38.1      |
| Weight (kg.)                                     | 0.9               | 0.9                       | 2                         | 2.7                       |
| <b>Environmental</b>                             |                   |                           |                           |                           |
| Operating Temperature (°C)                       | 0 - 35            | 0 - 35                    | 0 - 35                    | 0 - 35                    |
| Operating Relative Humidity (Non-condensing) (%) | 0 - 95            | 0 - 95                    | 0 - 95                    | 0 - 95                    |
| <b>Certifications</b>                            |                   |                           |                           |                           |
| Certifications*                                  | CE, UL60950       | CE, UL60950               | CE, UL60950               | CE, UL60950               |
| RoHS                                             | Yes               | Yes                       | Yes                       | Yes                       |

\*Certifications may vary according to different regions. Visit [www.cyberpower.com](http://www.cyberpower.com) for more information.  
#All specifications are subject to change without notice.